

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2009

Revision: 16.12.2008

1 Identification of substance

- **Product details**
- **Trade name** Elastoflex Facade Paint
- **Article number:** 2976
- **Application of the substance / the preparation** Coating
- **Manufacturer/Supplier:**
Remmers Baustofftechnik GmbH
Postfach 1255
D-49624 Lönningen / Germany
Tel.: 05432/83-0
Fax: 05432/3985
- **Informing department:**
Product Safety department: Tel.: +49 (0)5432/83-138/-538
E-Mail: sales@remmers.co.uk
- **Emergency information:**
during working hours:
U.K.: Tel.: +44 (0) 845 373 0103
Far East: Tel.: +65(0) 67410277
Head Office Germany: Tel.: +49 (0)5432 83 185
after working hours: Tel.: +49 (0)171/6428-297

2 Hazards identification

- **Hazard designation:** not applicable
- **Information pertaining to particular dangers for man and environment** not applicable
- **Classification system**
The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Pure acrylate-copolymer dispersion coating material

· **Dangerous components:**

	Solvent naphtha (mineral oil), slight aromatic	Xn; R 65	≤1.0%
CAS: 55406-53-6 EINECS: 259-627-5	3-Iodo-2-propynylbutylcarbamate	Xn, Xi, N; R 20/22-41-50	≤0.5%

4 First aid measures

- **General information** Immediately remove any clothing soiled by the product.
- **After inhalation** No special requirements.
- **After skin contact**
Wash immediately with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact**
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
Seek medical treatment.

(Contd. on page 2)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2009

Revision: 16.12.2008

Trade name **Elastoflex Facade Paint**

(Contd. of page 1)

- **Information for doctor**
- **The following symptoms may occur:**
In case of prolonged/repeated exposure or in high concentrations:
Irritating effect on skin and eyes.
- **Treatment** symptomatic treatment

5 Fire fighting measures

- **Suitable extinguishing agents**
CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
Use fire fighting measures that suit the environment.
- **Special hazards caused by the material, its products of combustion or flue gases:**
May be released in case of fire
Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic substances cannot be excluded.
- **Protective equipment:**
Put on breathing apparatus.
Body protection

6 Accidental release measures

- **Person-related safety precautions:**
Particular danger of slipping on leaked/spilled product.
Ensure adequate ventilation
- **Measures for environmental protection:**
Do not allow product to reach sewage system or water bodies.
Do not allow to enter the ground/soil.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.

7 Handling and storage

- **Handling**
- **Information for safe handling:** Use only in well ventilated areas.
- **Information about protection against explosions and fires:** No special requirements.
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information on storage in a common storage facility:** none
- **Further information about storage conditions:**
Store cool and dry in tightly closed containers.
Protect from frost.
Protect from heat and direct sunlight.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during compilation were used as a basis.

(Contd. on page 3)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2009

Revision: 16.12.2008

Trade name **Elastoflex Facade Paint**

(Contd. of page 2)

- **Personal protective equipment**
- **General protective and hygienic measures**
Observe the usual precautionary measures when handling chemicals.
Immediately remove soiled, saturated clothing.
Keep away from food, beverages and animal feed.
Do not eat, drink or smoke while working.
Use skin protection cream for preventive skin protection.
Wash hands before pauses and after work.
Avoid contact with eyes and skin.
- **Respiratory equipment:** Not necessary if handled properly.
- **Protection of hands:** Protective gloves.
- **Material of gloves:** Nitrile rubber, NBR
- **Penetration time of glove material**
Break through time: max. 240 min (DIN EN 374).
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
Safety glasses
if there is a risk of splashes
- **Body protection:** Protective work clothing.

9 Physical and chemical properties:

· General Information

Form:	Viscous
Colour:	White
Odour:	Mild

· Change in condition

Melting point/Melting range:	Not determined
Boiling point/Boiling range:	Not determined

· **Flash point:** Not applicable

· **Danger of explosion:** Product is not explosive.

· **Density at 20°C:** 1.36 g/cm³

· **Solubility in / Miscibility with Water:** Fully miscible

· **pH-value at 20°C:** 8.5

· **Viscosity:**
dynamic at 20°C: 3000 mPas

· **Solvent content:**
Organic solvents: 0.0 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
No decomposition if handled and stored according to specifications.
- **Dangerous reactions:** No dangerous reactions known
- **Dangerous decomposition products:**
None if used properly.

(Contd. on page 4)

GB

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2009

Revision: 16.12.2008

Trade name **Elastoflex Facade Paint**

None if stored properly.

(Contd. of page 3)

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritating effect.
- **on the eye:** No irritating effect.
- **Sensitisation:** No sensitising effect known.
- **Additional toxicological information:**

The product is not subject to labelling based on the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to directions, the product does not have any harmful effects according to our experience and the information available.

12 Ecological information:

- **General notes:**
Water hazard class 1 : slightly hazardous to water.
Do not allow product to reach ground water, bodies of water or sewage system.
according to appendix 4 VwVwS

13 Notes on disposal:

- **Product:**
- **Recommendation**
Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage.
The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 20	aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

14 Transport information

- **Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)**
- **ADR/RID-GGVS/E Class:** -
- **Maritime transport IMDG/GGVSea:**
- **IMDG/GGVSea Class:** -
- **Air transport ICAO-TI and IATA-DGR:**
- **ICAO/IATA Class:** -

(Contd. on page 5)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 28.01.2009

Revision: 16.12.2008

Trade name Elastoflex Facade Paint

(Contd. of page 4)

- **Transport/Additional information:** Not a hazardous good according to the above regulations.

15 Regulatory information

- **Designation according to EC guidelines:**

Observe normal safety precautions for handling chemicals

The product is not subject to labelling in accordance with EC Guidelines and the Ordinance on Hazardous Materials (GefStoffV).

- **Product Code:** M-DF02

- **National regulations**

- **Water hazard class:**

Water hazard class 1: slightly hazardous to water.

according to appendix 4 VwVwS

- **Other regulations, limitations and prohibition ordinances**

Observe the usual protective measures when working and for storage.

16 Other information:

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Delivery specifications are found in the respective Technical Information Sheets.

- **Relevant R-phrases**

20/22 Harmful by inhalation and if swallowed.

41 Risk of serious damage to eyes.

50 Very toxic to aquatic organisms.

65 Harmful: may cause lung damage if swallowed.

- **Department issuing data specification sheet:** Product Safety department

GB