

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Revision: 02.12.2011

1 Identification of substance

- **Product details**
- **Trade name** Epoxy BH 100, Component A
- **Article number:** 0905
- **Application of the substance / the preparation** Coating
- **Manufacturer/Supplier:**
Remmers Baustofftechnik GmbH
Postfach 1255
D-49624 Lönningen / Germany
Tel.: 05432/83-0
Fax: 05432/3985
- **Informing department:**
Product Safety department: Tel.: +49 (0)5432/83-138/-538
E-Mail: sales@remmers.co.uk
- **Emergency information:**
during working hours:
U.K.: Tel.: +44 (0) 845 373 0103
Far East: Tel.: +65(0) 67410277
Head Office Germany: Tel.: +49 (0)5432 83 185
after working hours: Tel.: +49 (0)171/6428-297

2 Hazards identification

- **Hazard designation:**



Xi Irritant
N Dangerous for the environment

- **Information pertaining to particular dangers for man and environment**
R 36/38 Irritating to eyes and skin.
R 43 May cause sensitisation by skin contact.
R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Contains epoxy constituents. See information supplied by the manufacturer.
- **Classification system**
The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Modified epoxide resin

- **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) Xi, N; R 36/38-43-51/53	60-80%
CAS: 28064-14-4	Bisphenol-F-Epichlorhydrin-Harze MG < 700 Xi, N; R 36/38-43-51/53	10-20%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Xn; R 20/22	5-10%

(Contd. on page 2)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Revision: 02.12.2011

Trade name Epoxy BH 100, Component A

(Contd. of page 1)

CAS: 2461-15-6	[[[(2-ethylhexyl)oxy]methyl]oxirane	1-2.5%
EINECS: 219-553-6	Xi, N; R 36/38-43-51/53	

· **Additional information** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· **General information**

Immediately remove any clothing soiled by the product.
In case of irregular breathing or respiratory arrest, provide artificial respiration.

· **After inhalation**

Use a respiration bag or breathing device.
In case of unconsciousness bring patient into stable side position for transport.

· **After skin contact**

Wash immediately with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

· **After eye contact** Rinse opened eye for several minutes under running water.

· **After swallowing**

Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.

5 Fire fighting measures

· **Suitable extinguishing agents**

Water spray jet
Carbon dioxide
Foam

· **For safety reasons unsuitable extinguishing agents** Water with a full water jet.

· **Special hazards caused by the material, its products of combustion or flue gases:**

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen chloride (HCl)
further harmful conflagration gases and fumes

· **Protective equipment:** Wear self-contained breathing apparatus.

· **Additional information**

Cool endangered containers with water spray jet.
Collect contaminated fire fighting water separately. It must not enter drains.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· **Person-related safety precautions:**

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation

· **Measures for environmental protection:**

Do not allow product to reach sewage system or water bodies.
Do not allow to enter the ground/soil.

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.

GB

(Contd. on page 3)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Revision: 02.12.2011

Trade name **Epoxy BH 100, Component A**

(Contd. of page 2)

7 Handling and storage

- **Handling**
- **Information for safe handling:**
Use only in well ventilated areas.
Open and handle container with care.
- **Information about protection against explosions and fires:** Protect from heat.
- **Storage**
- **Requirements to be met by storerooms and containers:** Prevent any penetration into the ground.
- **Information on storage in a common storage facility:**
Store away from oxidizing agents.
Store away from food.
- **Further information about storage conditions:**
Store cool and dry in tightly closed containers.
Store container in a well ventilated position.
Protect from frost.
Protect from heat and direct sunlight.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during compilation were used as a basis.
- **Personal protective equipment**
- **General protective and hygienic measures**
Immediately remove soiled, saturated clothing.
Store protective clothing separately.
Keep away from food, beverages and animal feed.
Do not eat, drink or smoke while working.
Use skin protection cream for preventive skin protection.
Wash hands before pauses and after work.
Avoid contact with eyes and skin.
Do not inhale gases / vapours / aerosols.
- **Respiratory equipment:**
In case of insufficient ventilation, use respiratory protection:
Filter A (brown)
Only use ambient air independent respiratory equipment in pits, shafts and silos!
- **Protection of hands:** Long cuffed gloves
- **Material of gloves:** Nitrile rubber, NBR
- **Penetration time of glove material**
Break through time: max. 240 min (DIN EN 374).
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Tightly sealed safety glasses.
- **Body protection:** Protective work clothing.

9 Physical and chemical properties:

· General Information

Form:	Fluid
Colour:	milky

(Contd. on page 4)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Revision: 02.12.2011

Trade name **Epoxy BH 100, Component A**

(Contd. of page 3)

Odour:	Weak, characteristic
Change in condition	
Melting point/Melting range:	Not determined
Boiling point/Boiling range:	> 200°C
Flash point:	> 100°C
Danger of explosion:	Product is not explosive.
Density at 20°C	1.150 g/cm ³
Solubility in / Miscibility with Water:	Insoluble
Viscosity:	
dynamic at 20°C:	950 mPas
Solvent content:	
Organic solvents:	10.0 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
No decomposition if handled and stored according to specifications.
- **Materials to be avoided:** Strong acids, strong bases and strong oxidising agents.
- **Dangerous reactions** Exothermic polymerisation
- **Dangerous decomposition products:**
None if used properly.
None if stored properly.
May be released in fire:
Carbon monoxide and carbon dioxide
Hydrogen chloride (HCl)
Phenol

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	LD50	> 10000 mg/kg (Ratte)
Dermal	LD50	> 2000 mg/kg (Ratte)

- **Primary irritant effect:**
- **on the skin:** Irritates skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitisation:** Sensitisation possible by skin contact.
- **Additional toxicological information:**
The product shows the following dangers based on the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
Irritant
- **Sensitisation** May cause sensitisation by skin contact.

GB

(Contd. on page 5)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Revision: 02.12.2011

Trade name **Epoxy BH 100, Component A**

(Contd. of page 4)

12 Ecological information:

- **General notes:**

Water hazard class 2 : hazardous to water.

Do not allow product to reach ground water, bodies of water or sewage system.

according to appendix 4 VwVwS

13 Notes on disposal:

- **Product:**

- **Recommendation**

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

- **European waste catalogue**

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
20 01 28	paint, inks, adhesives and resins other than those mentioned in 20 01 27

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID and GGVs/GGVE (cross-border/domestic)**



- **ADR/RID-GGVs/E Class:** 9 (M6) Miscellaneous hazardous substances and articles.

- **Kemler Number:** 90

- **UN-Number:** 3082

- **Packaging group:** III

- **Danger sign:** 9

- **Special marking:** Symbol (fish and tree)

- **Designation of goods:** 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700))

- **Limited quantities (LQ)** LQ7

- **Tunnel restriction code** E

- **Maritime transport IMDG/GGVSea:**



- **IMDG/GGVSea Class:** 9

- **UN Number:** 3082

- **Label** 9

- **Packaging group:** III

- **EMS Number:** F-A,S-F

- **Marine pollutant:** Symbol (fish and tree)

(Contd. on page 6)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Revision: 02.12.2011

Trade name **Epoxy BH 100, Component A**

(Contd. of page 5)

· **Correct technical name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700))

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 9
 · **UN/ID Number:** 3082
 · **Label:** 9
 · **Special marking:** Symbol (fish and tree)
 · **Packaging group:** III
 · **Correct technical name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700))

15 Regulatory information

· **Designation according to EC guidelines:**

The product has been classified and labelled in accordance with EC Guidelines / Ordinance on Hazardous Materials (GefStoffV)

· **Code letter and hazard designation of product:**



Xi Irritant
 N Dangerous for the environment

· **Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
 Bisphenol-F-Epichlorhydrin-Harze MG < 700
 [[(2-ethylhexyl)oxy]methyl]oxirane

· **Risk phrases:**

36/38 Irritating to eyes and skin.
 43 May cause sensitisation by skin contact.
 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Safety phrases:**

2 Keep out of the reach of children.
 24/25 Avoid contact with skin and eyes.
 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 37 Wear suitable gloves.
 46 If swallowed, seek medical advice immediately and show this container or label.
 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

· **Special labelling of certain preparations:**

Contains epoxy constituents. See information supplied by the manufacturer.

· **Product Code:** RE 1

· **National regulations**

· **Water hazard class:**

German Water hazard class 2: hazardous to water.
 according to appendix 4 VwVwS

GB

(Contd. on page 7)

Material Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 02.12.2011

Revision: 02.12.2011

Trade name Epoxy BH 100, Component A

(Contd. of page 6)

16 Other information:

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

· Relevant R-phrases

20/22 Harmful by inhalation and if swallowed.

36/38 Irritating to eyes and skin.

43 May cause sensitisation by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Department issuing data specification sheet: Product Safety department

GB