

Technical Information Sheet  
Article No. 2400-01

# Aidol

## Decorative Wax Stain

Group III wax stain for treating the surface of wood in indoor areas

### Range of use

For all types of wood in interior areas, e.g. walls, ceilings, furniture, also in damp rooms such as baths and showers, etc.

### Property profile

Aidol Decorative Wax Stain is an emulsion that is produced in a special process using beeswax, natural resins and boiled linseed oil. The product is in a brushing consistency and just one coat protects and maintains the wood surface, giving it a velvety touch. Due to natural raw materials, slight deviations in the colour of the product may occur which, according to our experience, do not have any influence on the colour of the wood surface. The texture of the wood remains visible because of its stain character. Tested according to DIN EN 71-3 "Safety for toys – Migration of certain elements".



### Characteristic data of the product

Density:	approx. 1.02 g/cm <sup>3</sup> at +20 °C
Odour:	typical for a wax stain
Packaging:	0.75 l and 2.5 l tin cans
Colours:	2400 clear, 2401 white

### Directions

Apply with a brush or soft linen cloth. The wood surface must be clean, dry and free of dust. Aidol Decorative Wax Stain can be applied without priming and it should be applied only in thin coats. A trial coating is recommended.

### Notes

Aidol Decorative Wax Stain does not impart the specific yellow colour of beeswax, even on light coloured types of wood. The natural texture of all types of wood is preserved and enhanced.

### Tools, cleaning

Clean brushes immediately after use with water and a detergent. Dispose of the remains from cleaning properly.

### Application rate

Depending on the absorbency of the substrate, between 50 - 150 ml/m<sup>2</sup> surface is required. If applying more than one coat, less is needed for the second and third coats.

### Drying

Depending on the application rate, type of wood and absorbency of the substrate, drying takes 2-5 hours.

Thorough drying is achieved after approx. 12 hours, depending on the substrate.

### VOC content

EU limit value for the product (Cat. A/e): 150 g/l (2007).  
This product contains max. 130 g/l VOC.

### Shelf-life

At least 2 years in closed, original containers stored dry and frost-free. Storage temperature should not be less than +5 °C and storage at temperatures above +40 °C is not advisable. The consistency of Aidol Decorative Wax Stain is thicker at lower temperatures.

### Composition

Copolymer dispersion, natural resin, wax, white spirit, titanium dioxide, water

Preservative: isothiazolinon

### Safety data/disposal

Keep out of reach of children. Do not inhale sprayed mist. Ensure adequate ventilation during and after work. In case of contact with eyes or skin, rinse immediately and thoroughly with plenty of water. Do not lead into the sewer system, aquatic environments or the ground. Only completely empty cans should be recycled. Liquid leftovers should be brought to collection facilities for old varnishes for disposal.

Product Code: M-KH 01

### Labelling

Water hazard class:  
1 (self-assessment)  
Regulations on hazardous substances: not applicable  
GGVS/ADR: not applicable