

Technical Information Sheet Article No. 2625-26

Aidol Weather Protection Oil

Water repelling coating for wood used in gardens

Range of use

Aidol Weather Protection Oil can be used anywhere where a special water repelling effect is needed to protect the beauty of wood. The oil is particularly suitable for treating pressure impregnated wood in outdoor areas such as wattle-work fences and other wood building elements in gardens.

Property profile

Through the use of special raw materials, treated wood has a water repelling, open pored surface that prevents the penetration of water. Aidol Weather Protection Oil is easy to apply and very high yielding. The oil contains a preservative to protect the film from microbial infestation (alga, mould, etc.).

Directions

The wood must be dry and free of dust, dirt, grease and wax. Sand loose and weathered old coatings. Apply two coats of undiluted Aidol Weather Protection Oil in the direction of the grain with a brush. Remove oil that has not been absorbed after approx. 30-60 minutes. Stir Aidol Weather Protection Oil well before using, during work and after pauses. Check the colour

Characteristic data of the product

Density:	approx. 0.83 g/cm ³ at 20 °C
Flash point:	approx. 63°
Packaging:	5 l tin containers
Colours:	2625 medium brown, 2626 salt green

and compatibility with the substrate with a trial coating.

Notes

Aidol Weather Protection Oil should only be used for the intended purpose and according to directions. Avoid contact with eyes and skin. Do not eat, drink or smoke when working. Do not store this product together with food or animal feed. Textiles (e.g. cleaning rags, work clothes) soiled with Aidol Weather Protection Oil may self-ignite so collect in fire resistant refuse containers and dispose of properly.

Tools, cleaning

Clean tools immediately after use with V 101 Thinner and dispose of the remains from cleaning properly.

Application rate

Approx. 100 ml/m² per coat.

Drying

Dust dry: after approx. 4 hours

Coated over: after approx. 24 hours

Practice values at 20 °C/65% relative humidity.

Thinning

If necessary, thin with V 101 Thinner or turpentine substitute.

Safety data

Danger warning:

Repeated contact may cause dry or cracked skin.

Safety advice:

In case of accident or illness, seek medical attention immediately (show label if possible).

Keep out of reach of children.

Do not inhale vapour/aerosol.

Avoid contact with skin.

Use only in well ventilated areas.

Contains cobalt octoate. May cause allergic reactions.

Product Code: M-KH 03

Disposal

Dispose of product remains in compliance with valid regulations. Completely empty containers should be recycled.

Ecology

Do not lead into aquatic environments, the sewer system or the ground.

Water hazard class (WGK):2

Labelling

Regulations on hazardous substances: n.a.

GGVSE/ADR: n.a.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.

Remmers India Pvt. Ltd.
Gurgaon
Tel.: +91 124 400 9131
Fax: +91 124 400 9134
www.remmers.in



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44(0) 845 373 0103
Fax: +44(0)845 373 0104
www.remmers.co.uk

Remmers (Far East) Pte. Ltd.
Singapore
Tel: +65 6 7410277
Fax: +65 6 7417158