



Technical Data Sheet Art. No. 2652-55

Maintenance Oil

Maintenance oil on a linseed oil base

Range of use

Maintenance Oil can be used everywhere where a special water-repelling effect is needed to maintain the beauty of the wood. It is especially suitable for treating garden furniture and wood decks made of teak, bangkirai, larch, Douglas fir, thermally treated wood and WPC.

Property profile

Through the use of special raw materials, the oil protects wood by creating a water-repelling, open-pored surface that prevents the penetration of water. Maintenance Oil is easy to apply, very high yielding and protects wood from drying out.

It also corresponds to the requirements of DIN EN 71-3, Safety for toys.

Directions

The wood must be dry and free of dust, dirt, grease and wax. Sand flaking and weathered old coatings. Prime soft wood as well as all other species of wood sensitive to fungi in outdoor areas with a wood preservative.

Apply two coats of undiluted Maintenance Oil in the direction of the grain using a brush. Material that has not been absorbed after 30 to 60 minutes should be taken up

Characteristic data of the product

Density:	approx. 0.83 g/cm ³ at 20°C
Flash point:	approx. 63°C
Packaging:	0.75 l, 2.5 l, 5 l tin cans
Colours:	2652 clear, 2653 teak, 2654 larch, 2655 bangkirai 2656 special colours

with a dry brush. Stir well before using, also during work and after pauses. Check colour and compatibility with the substrate with a trial coating.

Notes

Water soluble substances in species of wood such as oak, Australian blackwood, teak, bangkirai, larch, Douglas fir, etc. may bleed when subjected to precipitation which can cause stains on the wood as well as on light-coloured masonry work or render.

Maintenance Oil should only be used for the intended purpose and only according to directions. Keep out of reach of children. Avoid contact with skin and eyes. Do not eat, drink or smoke when working. Do not store together with food or animal feed. When working in interior spaces, ensure good ventilation.

Textiles (e.g. cleaning rags, work clothes) soiled with Maintenance Oil may have a tendency to self-ignite, so collect in fire resistant refuse containers and store under water until disposed of.

Clear Maintenance Oil does not protect wood from UV-rays (which can cause wood to turn grey) and should thus only be used for wood elements that are not directly exposed to weather (wood that is protected from direct sunlight, rain and wind). If a clear coating is desired in weathered outdoor areas, apply several coats and re-coat in regular intervals.

Tools, cleaning

Clean tools immediately after use with a V 101 Thinner and dispose of the remains from cleaning properly.

Application rate

Approx. 100 ml/m² per coat.

Drying

Dust dry: approx. 4 hour
Coated over: approx. 24 hours

Practice values at 20 °C/65 %
relative humidity.

Shelf-life

At least 5 year in closed, original
containers stored dry, cool and
protected from frost.

Safety data

Danger warnings:

May be harmful for aquatic organ-
isms with a long-term harmful ef-
fect.

Repeated contact may cause skin
to dry out and crack.

Safety advice:

Keep out of reach of children.
Do not release into the environ-
ment.

Product Code: M-KH 03

Disposal

Dispose of larger quantities of
leftover product in the original con-
tainer in compliance with valid
regulations. Completely empty
containers should be recycled. Do
not dispose of together with
household waste. Do not allow to
reach the sewer system.

Ecology

Do not allow to reach aquatic envi-
ronments, the sewer system or the
ground. Water hazard class
(WGK):2

Labelling

ADR: n.a.

The statements above are compiled from our field of
production and according to the latest technological
developments and application techniques.

Since application and working are beyond our control, no
liability of the producer can be derived from the contents of
this information sheet. Any statements made beyond the
contents of this information must be confirmed in writing
by the producer.

In all cases, our general conditions of sale are valid.
With the publication of this Technical Information Sheet all
previous editions are no longer valid.

2652-55 Maintenance Oil_11.16



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44 (0) 1293 594 010
Fax: +44 (0) 1293 594 037
www.remmers.co.uk