

Viscacid[®] MEDIUM QUARTZ AGGREGATE



Article No. 4417

Special combination of fire-dried, washed quartz aggregate.

Property profile:

Special combination of fire-dried, washed quartz aggregate.

Range of use:

Quartz aggregate for the production of scratch coats and filling compounds. Also for use as blinding agent on fresh coatings to achieve slip retardant properties (please observe test reports).

Grain size:

Quartz Aggregate 0.2-0.7 mm: Art.Nr. 4417
Quartz Aggregate 0.2-1.0 mm: Art.Nr. 4044

Characteristic data of the product:

Form: solid
Odour: odourless
Colour: white-yellowish
Density: 2.65 g/cm³

Directions:

Filler:

The two components A and B of Viscacid Epoxy Construction Resin are mixed thoroughly and then the filler is added. When working with larger amounts, the employment of a positive mixer is recommended.

Blinding agent:

For the production of slip retarding covers, the material is evenly spread over the fresh coating until saturation.

Packaging, application rate and storing:

Packaging: 25 kg bags

Application rate: depending on the chosen range of use

Shelf-life: Indefinitely when stored dry.

Safety, ecology, disposal:

Further information concerning safety during transport, storage and handling as well as for disposal is found in the latest Safety Data Sheet.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet.

Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid.

With the publication of this Technical Information Sheet all previous editions are no longer valid.