



Technical Information Sheet Article No. 5236

Rotec – Whirl Jet 18 litre System

Pneumatic 18 l

Range of use

Adjustable low pressure blasting machine for fine to medium hard blasting agents, especially Remmers Glass Powder (Art.-Nr. 5277 – 5280). The special Rotec turbine creates a rotating, conical cleaning area. Due to this effect typical building dirt and biological growth can even be removed gently from soft and morbid substrates.

Constituents

- self-closing, fast closing cone
- granulate metering valve
- 1" pressure reducer
- cyclone water separator, maintenance-free
- pneumatic remote control
- sieve
- lid
- 2 Druckluftports
- geräuschfrei im Ruhezustand

Characteristic product data

Technical data

Tank content:	18 Liter
Total height:	730 mm
Tank diameter:	260 mm
Total diameter:	550 mm
Weight:	30 kg
Pipework:	½"
Jet pressure:	0,1 – 7 bar

10 m jetting hose set consisting of:

- 10 m jetting hose 13 x 6 mm with couplings
- 10 m control cable
- 10 m HP hose with connections M22 x 1.5 / 3/8"

rotec whirl jet nozzle, complete, 25 mm hose connection with 5/12 mm nozzle head and turbine 13° with 3 lamellas

HP unit 9/80 max. 60 bar, 220 V/50 Hz

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.

GB 5236 - 10.08.doc



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44(0) 845 373 0103
Fax: +44(0)845 373 0104
www.remmers.co.uk

Remmers (Far East) Pte. Ltd.
Singapore
Tel: +65 6 7410277
Fax: +65 6 7417158