



Epoxy Primer PF

Pigmented primer and base layer

Constituents

VOC content

58 g/l (according to ASTM-D 2369, SCAQMD-RULE 1113)

Directive 2004/42/EC ("Decopaint" Directive)

EU limit value for the product (Cat. A/j): max. 500 g/l (2010).
This product contains < 500 g/l VOC.

SVHC as per Regulation 1907/2006/EC ("REACH")

Does not contain (<0.1%)

Heavy metals pursuant to VdL Guideline 01

Not contained as constitutive ingredients

Total solids (Deutsche Bauchemie test method)

compliant

Legal requirements

Construction Products Regulation

CE marking as per EN 13813:2002 present
CE marking according to EN 1504-2:2004 available

Eco-labels, certificates, declarations

Emissions

Material has been tested for its emissions of volatile organic compounds as part of the annual ProfiCert monitoring in the SL Floor Deco Flake system structure in an emission chamber test and fulfils the requirements of the AgBB for emissions from building products, among others.

Suitability for use as per LEED

Category as per Credit IEQc4.2 - 2009:
Primers, Sealers and Undercoaters:
VOC-Limit: 100 g/l without water: compliant
Traffic coatings:
VOC limit: 100 g/l without water: compliant

[nh_zusaetzliche_info]

Template EPD from Deutsche Bauchemie e.V. available: Products based on epoxy-resin, group 4 (EPD-DBC-20220177-IBF1-EN)

Production site

Remmers GmbH
Bernhard-Remmers-Straße 13
DE - 49624 Lönninge

18.09.2024